




ELECTRIC VEHICLE BATTERY IDENTIFICATION & TRANSPORTATION, AFTER DAMAGE


Automotive batteries (12v, hybrid, and EV batteries) pose a risk if **not properly prepared and transported, using all necessary standard operating procedures**. This **danger can be higher** if the battery systems in the vehicles have been **compromised from an accident**. Lithium-ion batteries contain high-energy and present electrical, chemical, and thermal hazards.


Before Vehicle Collection

- 

Identify the type of car: gas powered, hybrid electric, plug-in hybrid, or fully electric. The VIN can be used to identify the type of car. If the car cannot be identified, assume it's electric.
- 


Hybrid electric (HEV) and electric vehicles (EV) should be **marked with "HAZARDOUS VOLTAGE" warnings**.
- 


Transportation drivers and loader operators should be **trained of the potential dangers** with HEV / EV batteries.
- 


HEV / EV specific **personal protective equipment (PPE)** should be available to all involved in the collection and intake of the vehicle.
- 

Qualified personnel should assess the type of damage the vehicle has and identify any vehicle at high risk of having a compromised battery compartment.

During Vehicle Collection


- 


Proper PPE must be worn, and qualified personnel must be present.
- 


HEV / EV "HAZARDOUS VOLTAGE" **warning signs must be applied** to multiple sides of the vehicle.
- 


Qualified personnel should **assess possible damage to batteries prior to loading the vehicle**, and the transportation team should look for physical damage and symptoms (fire, discoloration of voltage cables).

Vehicle On-Site and Check-In

- 

Follow vehicle manufacturer's process to make the vehicle electrically-safe.
- 

Remove hazardous voltage battery master disconnect service plug and zip tie it to the steering wheel.
- 

HEV / EV should be **placed in a segregated area** awaiting final dismantling.
- 

Removed high voltage batteries must be **safely stored** to prevent risk of thermal events.